


Specifications



MODELS	GS™-3390 RT		GS™-4390 RT		GS™-5390 RT	
MEASUREMENTS	Metric	US	Metric	US	Metric	US
Working height maximum*	12.10 m	39 ft	15.11 m	49 ft	18.15 m	59 ft
A Platform height maximum	10.10 m	33 ft	13.11 m	43 ft	16.15 m	53 ft
B Platform length:	3.89 m	12 ft 8 in	3.89 m	12.8 in	3.89 m	12 ft 8 in
outside, extended single deck	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in	5.34 m	17 ft 6.25 in
C outside, extended dual deck	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in
D Slide-out platform extension deck - front	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
E Slide-out platform extension deck - rear	1.22 m	4 ft	1.22 m	4 ft	1.22 m	4 ft
F Platform width - outside	1.83 m	6 ft	1.83 m	6 ft	1.83 m	6 ft
Platform height - stowed**	1.55 m	5 ft 1 in	1.80 m	5 ft 11 in	2.02 m	6 ft 7.5 in
G Height - stowed	2.71 m	8 ft 10.5 in	2.93 m	9 ft 7.5 in	3.15 m	10 ft 4 in
rails lowered	2.03 m	6 ft 7.75 in	2.25 m	7 ft 4.75 in	2.47 m	8 ft 1.25 in
H Length - stowed: single deck	3.94 m	12 ft 11.25 in	3.94 m	12 ft 11.25 in	—	—
dual deck	3.98 m	13 ft .5 in	3.98 m	13 ft .5 in	—	—
with outriggers	4.88 m	16 ft	4.88 m	16 ft	4.88 m	16 ft
Length - extended: single deck	5.40 m	17 ft 8.5 in	5.40 m	17 ft 8.5 in	5.40 m	17 ft 8.5 in
dual deck	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in	6.57 m	21 ft 6.5 in
super deck	7.38 m	24 ft	7.38 m	24 ft	7.38 m	24 ft
I Width - standard tyres	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m	7 ft 6 in
high flotation tyres	2.57 m	8 ft 5 in	2.57 m	8 ft 5 in	2.57 m	8 ft 5 in
J Wheelbase	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in	2.84 m	9 ft 4 in
K Ground clearance - centre	36 cm	1 ft 2 in	36 cm	1 ft 2 in	36 cm	1 ft 2 in

PRODUCTIVITY						
Max platform occupancy	7	7	7	7	4	4
Lift capacity	1,134 kg	2,500 lbs	680 kg	1,500 lbs	680 kg	1,500 lbs
Drive speed - stowed	6.4 km/h	4.0 mph	6.4 km/h	4.0 mph	6.4 km/h	4.0 mph
Drive speed - raised	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph
Gradeability***	50%	50%	50%	50%	40%	40%
Turning radius - inside	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in	2.16 m	7 ft 1 in
Turning radius - outside	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in	5.33 m	17 ft 6 in
Controls	proportional	proportional	proportional	proportional	proportional	proportional
Raise / lower speed	45 / 29 sec	45 / 29 sec	45 / 39 sec	45 / 39 sec	55 / 49 sec	55 / 49 sec
Tyres - foam-filled rough terrain	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in	30 x 84 cm	12 x 33 in

POWER						
Power source	Deutz diesel D2011L03i 49 hp (36 kW), air cooled/ Ford DSG-423 4 cylinder petrol/LPG 75 hp (56 kW)					
Fuel tank capacity	113.6 L	30 gal	113.6 L	30 gal	113.6 L	30 gal
Hydraulic system capacity	113.6 L	30 gal	113.6 L	30 gal	113.6 L	30 gal

WEIGHT****						
	5,533 kg	12,198 lbs	5,949 kg	13,115 lbs	7,615 kg	16,788 lbs
Unit weight modifiers for options						
Outriggers*****	add 760 kg	1,676 lbs	add 780 kg	1,720 lbs	—	—
Dual Extension decks	add 165 kg	364 lbs	add 165 kg	364 lbs	add 165 kg	364 lbs
Super deck	add 220 kg	485 lbs	add 220 kg	485 lbs	add 220 kg	485 lbs
Non marking tyres RT	add 466 kg	1,027 lbs	add 466 kg	1,027 lbs	add 466 kg	1,027 lbs

STANDARDS COMPLIANCE	CE EN280, PB-10-611-03
----------------------	------------------------

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.
 ** Based on RT tyres. Deduct 5.8 cm (2 in) non-marking tyres.
 *** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.
 **** Weight will vary depending on options and/or country standards
 ***** Standard on GS-5390RT and with super deck.

Features

STANDARD FEATURES

MEASUREMENTS

GS™-3390 RT

- 12.06 m (39 ft) working height
- Up to 1,134 kg (2,500 lb) lift capacity

GS™-4390 RT

- 15.11 m (49 ft) working height
- Up to 680 kg (1,500 lb) lift capacity

GS™-5390 RT


- 18.15 m (59 ft) working height
- Up to 680 kg (1,500 lb) lift capacity

PRODUCTIVITY

- 3.94 x 1.83 m (12 ft 11.25 in x 6 ft) steel frame platform
- 1.52 m (5 ft) slide-out extension deck
- Replaceable aluminium deck
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Two self-closing gates
- Automatic levelling hydraulic outriggers (GS™-5390)
- Oscillating axle (GS™-3390)
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tyres
- Tilt sensor with audible alarm
- Descent alarm
- Horn
- Hour meter
- Certified load sensor

POWER

- Deutz diesel 49 hp (36 kW)
- Hydraulic oil cooler



OPTIONS & ACCESSORIES

PRODUCTIVITY

- Dual slide-out extension deck package 1.52 m (5 ft) front and 1.22 m (4 ft) rear
- 7.30 m super deck extension package*
- Automatic levelling hydraulic outriggers (GS™-3390 & GS™-4390)
- Oscillating axle (GS™-4390 & GS™-5390)
- Lift capacity 800 kg (GS™-4390 with outriggers and one extension only)
- Air line to platform
- Non-marking, foam filled tyres
- Dual flashing beacons
- Motion alarm
- Platform work lights

*Standard in UK

POWER

- Ford petrol/LPG 75 hp (56 kW)
- 2000 watt generator (110 V / 60 Hz)
- Cold weather packages for all engines (not CE)
- Biodegradable hydraulic oil
- Diesel scrubber/spark arrestor
- Diesel spark arrestor (without scrubber)
- LPG steel tank only, 15 kg (33.5 lb) capacity

UK

The Maltings
Wharf Road
Grantham NG31 6BH
UK
Tel: +44 (0)1476 584333
Fax: +44 (0)1476 584334

France

10, ZA de la Croix St. Mathieu
28320 Gallardon
France
Tel: +33 (0)2 37 26 09 99
Fax: +33 (0)2 37 26 09 98

Germany

Finienweg 3
28832 Achim/Bremen
Germany
Tel: +49 (0)4202 8852-0
Fax: +49 (0)4202 8852-25

Spain

Gaià 31, Pol. Ind. Plá d'en Coll
08110 Montcada i Reixac
Barcelona
Spain
Tel: +34 93 572 50 90
Fax: +34 93 572 50 91

Scandinavia

Aröds industriväg 34
422 43 Hisings Backa
Sweden
Tel: +46 31 57 51 00
Fax: +46 31 57 51 04

Middle East

Terex Middle East
PO Box 282325, Dubai
U.A.E.
Tel: +971 4 885 8030
Fax: +971 4 885 6364
Email: awp.infome@terex.com

Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, WA
USA 98073-9730
Tel: +1 425 881-1800
Fax: +1 425 883-3475

Email: AWP-InfoEurope@terex.com

Distributed By: