# ZOOMLION

## **EXTENDED-RANGE HYBRID** TELESCOPIC BOOM LI ZT21JEH-V

**Comply with CE Standard** 



## **HIGHLIGHTS**

- - - ► Accurate and effective drive system, strong power, stable control, and motor maintenance free
      - ► High frequency and low amplitude response control technology, click to move with buffer
        - ► Compact design and folded jib for wrecker
          - ▶ Parallel four link and three compact structure
- ► Load-sensitive and engine condition matching energy-saving technology, as well as the boom self-weight lowering function, energy consumption reduced by 18% compared to conventional technology

► Controller remote upgrade and

high service efficiency

mobile parameter adjustment for



**FEATURES** 

Telecommunications System
Hom
Proportional control
All motion alarm
Flashing beacon
Self-closing entry gate
Emergency descent system
Emergency stop button
Auto-leveling system
On-board diagnostic system
Tilt protection system
Oscillating axle
Load sensing system
Remote monitoring and rental management platform

- ► Anti-collision device

## **Accessories & Options**

- ▶ Platform work light
- ► AC power to platform

- ▶ 6kw large power range extender provides power in low electric quantity
  - ▶ New off-road chassis, gradeability of 45%, strong obstacle climbing ability
    - - - and container transportation
          - telescopic boom sections for dynamic CG adjustment and



## **ACCESS WITH ZOOMLION GREEN**

Phone: 0086(731)-88353692

Add: 701 Xulong Nan Lu, Xiangjiang New District, Changsha Hunan, China


### **ZOOMLION**

Model	ZT21JEH-V
Size	
Work Height	22.95m
Platform Height	20.95m
Horizontal Outreach	15.5m
A Overall Length (Stowed)	9.4m (6.8m)
B Overall Width (Stowed)	2.46m
C Overall Height (Stowed)	2.7m
D Platform Length	2.44m
E Platform Width	0.91m
F Wheelbase	2.52m
Track width	2.46m
G Ground Clearance	0.33m
Perform	ance
Platform Capacity	300/454kg
Drive Speed (stowed)	5.2km/h
Gradeability	45%(24°)
Turning Radius (Inside)	2.69m
Turning Radius (Outside)	5.45m
Turntable Rotation	360° continuous
Platform Rotation	±90°
Tail Swing	1.7m
Jib Rotation	130° ( - 55°~75°)
Max. Wind Speed	12.5m/s

Platform Rotation	±90°	
Tail Swing	1.7m	
Jib Rotation	130° ( - 55°~75°)	
Max. Wind Speed	12.5m/s	
Power		
Battery	51.2V/315Ah	
Range Extender	6kW	
Charger	48V / 60A	
Drive Motor	3.3kW	
Lift Motor	10kW	
Auxiliary power	12V DC	
Fuel Tank	105L	
Hydraulic Tank Capacity	75L	
Tir	e	
Tire Type	Foam-filled tire	
Weight		
Gross	10600kg	







Range of Motion ZT21JEH-V